

Multilock Steel Stoppers for closing pipes during welding work



General Description

For closing off Oil and Gas Pipelines whilst welding or other repair work is carried out.

Features and Benefits


Pressure Plates are made of steel plate. Rubber Seals are commercial grade rubber mouldings.

Options

Pressure Gauge can be fitted for ease of checking the pressure in the pipeline.

A 2nd 1" Outlet can be fitted to the top of the Stopper. This is fitted with a Hose Coupling. A 3m Hose is fitted to this Coupling to allow gases to be vented out or the Pipe during welding work to avoid the risk of explosion.

Stoppers can be supplied with Double Seals to make the Stoppers more stable in the Pipe. Chemical resistant Rubber Seals can be supplied.



Multilock Steel Stoppers for closing pipes during welding work

Specification and Dimensions

Dia Inch	Pipe Min	ID Max	Insert Into Pipe	Water Way	Maximum Pressure	Weight of Plug	Length of Plug
10"	239	275	100mm	2"	5p.s.i.	9.0 kg	130mm
12"	298	320	100mm	2"	5p.s.i.	9.0 kg	130mm
14"	348	400	100mm	2"	5p.s.i.	9.0 kg	130mm
16"	384	450	100mm	2"	5p.s.i.	9.0 kg	130mm
18"	435	482	100mm	2"	5p.s.i.	9.0 kg	130mm
20"	480	530	100mm	2"	5p.s.i.	10.5 kg	130mm
22"	535	578	100mm	2"	3p.s.i.	12.0 kg	130mm
24"	590	640	100mm	2"	3p.s.i.	16.0 kg	130mm
26"	635	690	100mm	2"	3p.s.i.	18.0 kg	130mm
28"	690	740	100mm	2"	3p.s.i.	21.5 kg	130mm
30"	740	786	100mm	2"	3p.s.i.	26.0 kg	130mm
32"	785	835	100mm	2"	3p.s.i.	29.5 kg	130mm
34"	825	880	100mm	2"	3p.s.i.	32.0 kg	130mm
40"	990	1040	100mm	2"	3p.s.i.	42.0 kg	130mm
46"	1140	1190	100mm	2"	3p.s.i.	62.0 kg	130mm